

→ Location assessment → Estimation of cost-effectiveness or profitability → Equipment selection → Design of the structure

→ Construction of the plant/facility → Installation and putting into operation → Training and technical documentation → Servicing

IDEAL SOLUTION FOR WASHING COMMERCIAL VEHICLES



MOBIWASH™
PROFESSIONAL
TRUCK WASHING SYSTEM



MOBIWASH

E-mail: office@mobiwash.eu • www.MOBIWASH.eu

MOBIWASH™

Mobile Washing System
MW 3600I Professional

SIGURNOSNI
PREKIDAČ

GLAVNI PREKIDAČ

ŠAMPONIRANJE

MW 3600I PROFESSIONAL



MW Professional Bus. Semi-automatic washing facility with one brush made of inox for quick and efficient wash urban, interurban or smaller van-buses.

Semi-automatic washing facility with one brush for quick and efficient wash. This is an easy-to-operate, washing facility of 3630 mm for washing urban, interurban buses and other commercial vehicles. Easy operation ensures maximum efficiency in vehicle washing. This semi-automatic washing facility is an ideal solution for fast and thorough cleaning of the side, front and rear parts of the vehicle. All parts are carefully selected to ensure long lasting and safe operation of the machine. Also all parts are laboratory tested and guarantee the highest level of safety for the operator and the environment, the installation management system will, besides the safety, enable easy operation.

Reliable and massive construction is made of stainless-steel in state of art modern design. This material guarantees the best protection against corrosion and resistance to all kind of weather conditions.

The machine is powered by a gear motor.

An incline of up to 10%, which is simply adjusted by a button on the side of the washing plant, within the double command system is available on both sides, thus it will allow the brush to reach the vehicle to the optimum extent and maximize the efficiency of washing.

The brush made of profiled polyethylene fibers, 0.6 mm thickness, during the washing process creates a volume of 900 mm, and thus guarantees the best efficiency. The spray protection of the rotating brush is made of a XT acryl extruded plate 2mm thickness. This extraordinary material aside its brilliant look whose structure brings state of art transparency and clear picture of the brush work during washing process also has very high degree of bending resistance and UV protection.

Washing facility is moved by aluminum wheels with bearings and rubber lining which contributes to longevity and very low wearing degree. They are distinguished by their massive, resistant tread and extremely easy manipulation. The limit of soft rubber wheels makes it easy for the operator to maintain the optimal distance between the machine and the vehicle for efficient brush work.

TECHNICAL INFORMATION

Washing height	3630 mm
Number of phase currents	3
Voltage current	400V
Frequency	50Hz
Connection	5x2,5mm ²
Fuses	16A
Voltage of the command set	24V
IP Protection Class	IP 56
Network water supply	3/4"
Water pressure	6 bar
Water temperature	min 4 °C max 40 °C



POWER SUPPLY

Industrial plug reliable in use indoor and outdoor space. Provides a reliable connection and a high degree of protection of personnel from electricity.




DOUBLE COMMANDS

Commands at the both sides of the machine, positioned at the control handle. They regulate the inclination and direction of movement of the brush.



WATER SUPPLY

Quick coupling allows quick and safe connection of water supply.



WATER AND SHAMPOO APPLICATION

Sprayers arranged on 2 strings, 10 sprinklers on each vertical provide uniform application of shampoos and water to the vehicle and brushes.